

Machine Specification | EXTERNAL USE

Motor Wattage:	2900 Watt (3 x 967)
Water Lift:	95"
Air Flow Movement:	9,166 LPM
Cyclonic Entry Port:	50mm
Container:	78 Litre
Weight:	83kg
Decibel Level:	74 dB
Mains Connection:	Engine Honda GX200
Dimensions (cm):	150(l) x 63(w) x 104(h)



Clamped Pole



POLE TYPE:	Premium 50mm CLAMPED
Material:	Carbon Fibre Hybrid
Weight per 1.5m:	350g
Diameter:	50mm
Length:	1.5m
Reach:	4 Storeys / 12m / 40ft



Patent Pending No: GB1713830.6

Tool Holder

EU Registered Design No: 008458913

Packages include (Available with 4, 6 or 8 poles)

CLAMPED Package:

- 1.5M Suction Poles (50mm) 1 x Vac Release Cuff 1 x Anti-Block Hairpin Neck tool holder
- 5M Wire Reinforced 50mm Suction Hose 5 x Gutter End tools 2 x Cuffs Carry bag for poles and accessories
- 2 x Guttersucker Van Stickers

Floor Tool kit: 3 x Brush Heads 1) Carpet 2) Hard floor 3) Water pick up. Handle (3 sections)

Key Features



ONBOARD HONDA ENGINE



50MM CYCLONIC SIDE ENTRY PORT



EASY TO TRANSPORT & MANEUVER



VACUUM TIPPING CHASSIS FOR EASY EMPTYING



VACUUM CAN BE REMOVED FROM THE CHASSIS